

# VERTICAL FEED MIXERS



## Features

- **Integrated Chassis** means a lighter machine with greater ground clearance, without compromising on the compact design.
- **Adjustable Draw Bar** allows the machine to remain level with the tractor and improves tracking and ground clearance.
- **Hydraulic Support Foot**, fitted to the draw bar, allows effortless hitching and unhitching without the operator leaving the tractor.
- **PTO Shaft** is matched to the size of the machine. The shear bolt prevents any damage to the tractor or machine in case of obstructions in the mixing tank.
- **Inspection Ladder** is positioned in the front of the machine, allowing safe viewing of the inside.

## Pick your extras

- **Electro-Hydraulic Remote Control**
- **Wide Angle PTO**
- **Extended Discharge Conveyor**
- **Additional Cutting Knives**
- **Hydraulic Counter Knives**
- **Automatic Counter Knives**

## Specifications

MODEL	MPX004	MPX006	MPX007	MPX009	MPX011	MPX013	MPX015	MPX018	MPX020	MPX022
CAPACITY (m <sup>3</sup> /h <sup>1</sup> )	4 (141)	6 (212)	7 (247)	9 (318)	11 (388)	13 (458)	15 (528)	18 (636)	20 (706)	22 (777)
CAPACITY (kg/lbs)	1000 (2205)	1500 (3307)	1750 (3858)	2250 (4968)	2750 (6063)	3250 (7165)	3750 (8267)	4500 (9921)	5000 (11023)	5500 (12125)
LENGTH (m m/ft)	3900 (153-9/16)	4200 (165-3/8)	4400 (173-1/4)	4450 (175-3/16)	4750 (187)	4900 (192-15/16)	5150 (202-3/4)	6800 (267-3/4)	7100 (279-9/16)	7100 (279-9/16)
WIDTH (m m/ft)	2100 (82-11/16)	2100 (82-11/16)	2100 (82-11/16)	2100 (82-11/16)	2350 (92-9/16)	2350 (92-9/16)	2500 (98-7/16)	2100 (82-11/16)	2350 (92-9/16)	2350 (92-9/16)
HEIGHT (m m/ft)	1750(68-7/8)	2250(88-9/16)	2450(96-1/2)	2700 (106-5/16)	2700 (106-5/16)	2700 (106-5/16)	2950 (116-3/16)	2700 (106-5/16)	2600 (102-3/8)	2700 (106-5/16)
EMPTY WEIGHT (kg/lbs)	2400 (5291)	2900 (6317.3)	3000 (6614)	3200 (7055)	3600 (7937)	4000 (8818)	4400 (9703)	6000 (13228)	6400 (14113)	6500 (14333)
WHEELS	2 X 12.5 X 15.3	2 X 30 11 R 14.5	2 X 30 11 R 14.5	2 X 30 11 R 14.5	2 X 400/60 R 15.5	2 X 400/60 R 15.5	2 X 400/60 R 15.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5	2 X 435/50 R 19.5
NO. OF AUGERS	1	1	1	1	1	1	1	2	2	2
REQUIRED PTO RPM	540	540	540	540	540	540	540	540	540	540

Xeno

BOLANDAGRI FARMING

Tel: 071 533 4290 \* Epos: verkepe@bolandagri.co.za

www.bolandagri.co.za

