

HORIZONTAL MIXER



Features

- **Integrated Chassis** and integrated mixing bin mean a lighter machine with greater ground clearance, without compromising on the compact design.
- **Adjustable Draw Bar** allows the machine to remain level with the tractor and improves tracking and ground clearance.
- **Hydraulic Support Foot**, fitted to the draw bar, allows effortless hitching and unhitching without the operator leaving the tractor.
- **PTO Shaft** is matched to the size of the machine. The shear bolt prevents any damage to the tractor or machine in case of obstructions in the mixing tank.
- **Inspection Ladder** is positioned in the front of the machine allowing safe viewing of the inside.
- **Remote Cables** are fitted to the hydraulic control bank on the machine and mounted on the tractor, making it easy for the tractor operator to reach and operate the hydraulic functions of the mixer.

Pick your Extras

- **Electro-Hydraulic Remote Control**
- **Wide Angle PTO**
- **Extended Discharge Conveyor**

Specifications

MODEL	MFA007	MFA009	MFA012	MFA015	MFA018	MFA020
CAPACITY (m ³ /H ¹)	7 (247.2)	9.5 (335.5)	12 (423.8)	15 (529.7)	18 (635.7)	20 (706.3)
CAPACITY (kg/ha)	1750 (3858)	2375 (5236)	3000 (6614)	3750 (8247)	4500 (9923)	5000 (11023)
LENGTH (mm/inch)	4800 (189-15-1/4)	5350 (210-5/8)	5800 (228-3/8)	6250 (246-1/4)	6700 (263-13/16)	6900 (271-11/16)
WIDTH (mm/inch)	1800 (70-7/8)	1900 (74-13/16)	2200 (86-5/8)	2250 (88-9/16)	2500 (98-7/16)	2500 (98-7/16)
HEIGHT (mm/inch)	2300 (90-9/16)	2400 (94-1/2)	2500 (98-7/16)	2650 (104-3/8)	2750 (108-5/16)	2850 (112-1/4)
EMPTY WEIGHT (kg/lbs)	3900 (8598)	4300 (9480)	4700 (10362)	5300 (11685)	5900 (13007)	6400 (14110)
WHEELS	2 X 11.5/80 R 15.3	2 X 11.5/80 R 15.3	2 X 13.0/65 R 18	2 X 315/70 R 22.5	2 X 385/65 R 22.5	2 X 385/65 R 22.5
REQUIRED PTO RPM	540	540	540	540	540	540
RECOMMENDED POWER REQUIREMENT (kw/hp)	50/65	60/80	70/95	85/115	95/130	110/150

Argon

MODEL	MFA007B	MFA009B	MFA012B	MFA015B	MFA018B	MFA020B
ELECTRIC MOTOR (kw/hp)	37 (49.6)	45 (60.3)	55 (73.8)	75 (100)	90 (120)	90 (120)
CAPACITY (m ³ /H ¹)	7 (247.2)	9.5 (335.5)	12 (423.8)	15 (530)	18 (635.7)	20 (706.3)
CAPACITY (kg/ha)	1750 (3858)	2375 (5236)	3000 (6614)	3750 (8247)	4500 (9923)	5000 (11023)
LENGTH (mm/inch)	6800 (267-3/4)	7350 (289-3/8)	7800 (307-1/4)	8250 (324-13/16)	8700 (341-9/16)	8900 (350-7/16)
WIDTH (mm/inch)	1800 (70-15/16)	1900 (74-13/16)	2200 (86-5/8)	2250 (88-9/16)	2500 (98-7/16)	2500 (98-7/16)
HEIGHT (mm/inch)	2300 (90-9/16)	2400 (94-1/2)	2500 (98-7/16)	2650 (104-3/8)	2750 (108-5/16)	2850 (112-1/4)
EMPTY WEIGHT (kg/lbs)	4900 (10803)	5300 (11685)	5700 (12564)	6300 (13889)	6900 (15212)	7400 (16314)

Argon Bio

BOLANDAGRI FARMING

Tel: 071 533 4290 * Epos: verkoep@bolandagri.co.za

www.bolandagri.co.za

